

CLAIMS

1. A decoration panel installed on the walls which comprises a main panel 15 having a plurality of holes 20 aligned on the upper or lower part of it in the vertical direction, a sub panels 30, 40 having a front cover 31 and a plurality of holes 37a, 37b on the rear of the front cover 31 corresponding to the holes 20 and being inserted on the upper or lower end of the main panel 15, and a joiner 50 being engaged through the holes 37a, 37b of the sub panel 30, 40 into the holes 20 of the main panel 15 to join the sub panel 30, 40 to the upper or lower part of the main panel 15, and the length of the decoration panel being adjustable by selectively inserting the joiner 50 with the holes 20 of the sub panel 30 and the corresponding holes 20 of the main panel 15.

2. A decoration panel of claim 1, wherein the holes 20 are formed on the first strips 55 disposed on the upper or lower part of rear of the main panel 15 in a longitudinal direction, and the holes 37a, 37b are formed on the second strips 60 disposed on the rear of the front cover 31 of the sub panels 30, 40 in the longitudinal direction, and the edge plates 65, 66 are provided on the periphery of the main panel 15, and the upper

or lower edge plates 65 of the main panel 15 have recesses 70 corresponding to the first strips 55 so that the second strips 60 of the sub panel 30, 40 should be inserted on the recesses 70 when the sub panels 30, 40 are joined on the upper or lower end of the main panel 15.

3. A decoration panel of claim 1 or 2, wherein a plurality of horizontal score lines 75 are formed on the upper part or lower part of the main panel 15 so that the length of the main panel 15 should be adjustable by cutting the upper part or lower part of the main panel 15 along the score lines 75.